

What is claimed is:

1. A gas sensor which comprises:

a gas detecting section; and

5 a heater section secured in the gas sensor,

the heater section including a heating element and a support which supports at least the heating element,

wherein an opening section is provided to reduce pressure generated between the heating element and the support.

10

2. The gas sensor according to claim 1, wherein the opening section is provided so that at least a part of the support is exposed to an external atmosphere.

15

3. The gas sensor according to claim 2, wherein the heater section includes:

the heating element;

a lead electrically connected with the heating element;

and

20

the support which supports the heating element and the lead,

wherein the opening section is provided so that at least a part of a section, or vicinity thereof, of the support which supports the heating element is exposed to an external

25

atmosphere.

4. The gas sensor according to claim 1, wherein the heater

section includes:

the heating element;

a lead electrically connected with the heating element;

and

5 the support which supports the heating element and the lead,

wherein the opening section is provided so that at least a part of an interface between the heating element and the support or an interface between the lead and the support is
10 exposed to an external atmosphere.

5. The gas sensor according to claim 1, wherein the gas detecting section includes:

a solid electrolyte diaphragm; and

15 at least a pair of electrodes, the one electrode being disposed on one surface of the diaphragm and the other electrode being disposed on another surface of the diaphragm.

6. The gas sensor according to claim 2 wherein the gas
20 detecting section includes:

a solid electrolyte diaphragm; and

at least a pair of electrodes, the one electrode being disposed on one surface of the diaphragm and the other electrode being disposed on another surface of the diaphragm.

25

7. The gas sensor according to claim 3, wherein the gas detecting section includes:

a solid electrolyte diaphragm; and

at least a pair of electrodes, the one electrode being disposed on one surface of the diaphragm and the other electrode being disposed on another surface of the diaphragm.

5

8. The gas sensor according to claim 4, wherein the gas detecting section includes:

a solid electrolyte diaphragm; and

10 at least a pair of electrodes, the one electrode being disposed on one surface of the diaphragm and the other electrode being disposed on another surface of the diaphragm.

9. The gas sensor according to claim 5, wherein the solid electrolyte diaphragm includes stabilized zirconia.

15

10. The gas sensor according to claim 6, wherein the solid electrolyte diaphragm includes stabilized zirconia.

20 11. The gas sensor according to claim 7, wherein the solid electrolyte diaphragm includes stabilized zirconia.

12. The gas sensor according to claim 8, wherein the solid electrolyte diaphragm includes stabilized zirconia.

25 13. The gas sensor according to claim 1, which comprises an air inlet space.

14. The gas sensor according to claim 2, which comprises
an air inlet space.

15. The gas sensor according to claim 3, which comprises
5 an air inlet space.

16. The gas sensor according to claim 4, which comprises
an air inlet space.

10 17. The gas sensor according to claim 13, wherein the
opening section opens to the air inlet space.

18. The gas sensor according to claim 14, wherein the
opening section opens to the air inlet space.
15

19. The gas sensor according to claim 15, wherein the
opening section opens to the air inlet space.

20. The gas sensor according to claim 16, wherein the
20 opening section opens to the air inlet space.